

3/4自动网印机

3/4Automatic Screen Printing Machine

该机由印刷主机、丝网印刷自动出料机及光固机联机组成。是一款人工送料、自动出料形式的四分之三自动型丝网印刷生产线。当印刷主机印刷完成，印刷臂抬起后，出料机之机械臂自动伸入印刷臂与平台之间，将印刷平台上印刷完毕的印品吸住并拉出，送往下一工序（烘干、固化或收纸等）。在节约人力的同时，提高半自动丝印机的使用效率。该机适用于软质材料的丝网印刷，如纸质产品。

The machine is composed of printing part、take off set machine and UV dryer. It is a 3/4 automatic line which the printing stock is fed by hand、taken off automatically.

After the printing finished and the printing arm put up, the mechanism arm of take off set machine will extend into between the arm and the plane, suck and pull out the printing stock, then send it to next working procedure(drying、solidify or collection). It's not only can save the man, but also improve the using efficiency of the machine. It's fit for the flexible material, such as paper product.

技术参数 Technical Parameter

规格型号	Model	750IIc	960IIc	1280IIc
配套主机	Screen printing part	750II	960II	1280II
配套出料单元	Take-off set	800CL	800CL	900CL
配套固化单元	UV Part	800B	800B	900B
最高速度	Top speed	1100 pcs/h	1000 pcs/h	900 pcs/h
印品规格	Space of printing paper	700 × 500 mm ≤ 500 g/m ²	900 × 600 mm ≤ 500 g/m ²	1200 × 800 mm ≤ 500 g/m ²
装机功率	Power	3 Φ 380V 15.24Kw	3 Φ 380V 16.49Kw	3 Φ 380V 16.89Kw
整机重量	Total weight	1400 Kg	1530 Kg	1650 Kg
外型尺寸	Overall dimension	6.6 × 1.05 × 1.76m	6.8 × 1.18 × 1.76m	7.1 × 1.4 × 1.85m

